

## POLYURETHANE AIR HOSE

### FEATURES

- ◎ Suitable for push-to-connect fittings
- ◎ Variety color / size for vary demand



PART NO.	I.D(mm)	O.D(mm)	LENGTH	TEMPERATURE	WORKING PRESSURE at 70°F
HUS0508	5.0	8.0	100 M	-5°F~+140°F	120 PSI
HUS6510	6.5	10	100 M		
HUS0812	8.0	12	100 M		
HUS0406	4.0	6.0	200 M		
HUS2504	2.5	4.0	200 M		
HUS1015	1/8"	1/4"	300 FT		
HUS1020	3/16"	5/16"	300 FT		
HUS2030	1/4"	3/8"	300 FT		
HUS3040	5/16"	15/32"	300 FT		

### FEATURES

- ◎ Light and flexible
- ◎ Suitable for any quick coupler / connectors
- ◎ Variety color / size for vary demand
- ◎ OEM project are very welcome



PART NO.	I.D(mm)	O.D(mm)	LENGTH	PART NO.	I.D(mm)	O.D(mm)	LENGTH
HUR050805	5.0	8.0	5	HUR102020	3/16"	5/16"	20
HUR050810	5.0	8.0	10	HUR102030	3/16"	5/16"	30
HUR050815	5.0	8.0	15	HUR102050	3/16"	5/16"	50
HUR651005	6.5	10	5	HUR203020	1/4"	3/8"	20
HUR651010	6.5	10	10	HUR203030	1/4"	3/8"	30
HUR651015	6.5	10	15	HUR203050	1/4"	3/8"	50
HUR081205	8.0	12	5	HUR304020	5/16"	15/32"	20
HUR081210	8.0	12	10	HUR304030	5/16"	15/32"	30
HUR081215	8.0	12	15	HUR304050	5/16"	15/32"	50

## NYLON AIR HOSE

### NYLON AIR HOSE



#### FEATURES

- ◎ Strong & lightweight.
- ◎ High burst pressure standard

PART NO.	I.D(mm)	O.D(mm)	LENGTH	TEMPERATURE	WORKING PRESSURE at 70°F
HNS2504	2.5	4.0	200 M	-60°F~+200°F	225 PSI
HNS0406	4.0	6.0	100 M		
HNS0608	6.0	8.0	100 M		
HNS7510	7.5	10	100 M		
HNS0912	9.0	12	100 M		

### NYLON COILED AIR HOSE



#### FEATURES

- ◎ Lightweight and permanently coiled.
- ◎ Quality nylon formulation resists moisture absorption and abrasion.
- ◎ Each assembly is supplied with durable brass compression fittings, tube inserts and hose ferrules.
- ◎ Spring guards are also provided on all assemblies 3/4".

PART NO.	HOSE I.D	HOSE O.D	TEMPERATURE RANGE	WORKING PRESSURE at 70°F
HNR14	1/4"	.305/.313	-60°F~+200°F	185 PSI
HNR38	3/8"	.465/.475	-60°F~+200°F	165 PSI
HNR12	1/2"	.620/.630	-60°F~+200°F	170 PSI