

QUICK COUPLER

SPECIFICATION

MATERIAL	STAINLESS	STEEL	ZDC-2
WORKING PRESSURE	15 kgf/cm ²		10 kgf/cm ²
MAXIMUM PRESSURE	20 kgf/cm ²		15 kgf/cm ²
TEMP. RANGE	-20°C ~ +80°C		
SIZE	1/4" (20 type)		
	3/8" (30 type)		
	1/2" (40 type)		



APPLICATIONS


- ⊙ Pneumatic tools
- ⊙ Air piping
- ⊙ Air pressure equipment
- ⊙ Water piping

FEATURES


- ⊙ One-way automatic shut-off valve in the socket.
- ⊙ Wide variety provides best choice according to application.
- ⊙ Hardened important parts are extremely wear resistant and durable.
- ⊙ Tested 100,000 times, coupler connection is accurate and reliable.

Variety of connections

- ⊙ Hose stem H 
- ⊙ Female thread F 
- ⊙ Male thread M 



MATERIAL : STAINLESS / STEEL / ZDC-2


20SHA	5/16"(HOSE)			20PHA	5/16"(HOSE)
30SHA	3/8"(HOSE)			30PHA	3/8"(HOSE)
40SHA	1/2"(HOSE)			40PHA	1/2"(HOSE)
20SFA	1/4"(PT)			20PFA	1/4"(PT)
30SFA	3/8"(PT)			30PFA	3/8"(PT)
40SFA	1/2"(PT)			40PFA	1/2"(PT)
20SMA	1/4"(PT)			20PMA	1/4"(PT)
30SMA	3/8"(PT)			30PMA	3/8"(PT)
40SMA	1/2"(PT)			40PMA	1/2"(PT)
20SPA	5X8MM			20PPA	5X8MM
30SPA	6.5X10MM			30PPA	6.5X10MM
40SPA	8X12MM			40PPA	8X12MM

QUICK COUPLER

HIGH FLOW QUICK COUPLER : STEEL

SPECIFICATION

MATERIAL	STEEL
WORKING PRESSURE	15 kgf/cm ²
MAXIMUM PRESSURE	20 kgf/cm ²
TEMP. RANGE	-20°C~+80°C
SIZE	1/2" (400type)
	3/8" (600type)
	1" (800type)







APPLICATIONS

- ⊙ Pneumatic tools
- ⊙ Air piping
- ⊙ Air pressure equipment
- ⊙ Water piping

FEATURES

- ⊙ One-way automatic shut-off valve in the socket.
- ⊙ Wide variety provides best choice according to application.
- ⊙ Hardened important parts are extremely wear resistant and durable.
- ⊙ Tested 100,000 times, coupler connection is accurate and reliable.

	400SHA	1/2" HOSE
	600SHA	3/4" HOSE
	800SHA	1" HOSE
	400SFA	1/2" PT
	600SFA	3/4" PT
	800SFA	1" PT
	400SMA	1/2" PT
	600SMA	3/4" PT
	800SMA	1" PT
	400PHA	1/2" HOSE
	600PHA	3/4" HOSE
	800PHA	1" HOSE
	400PFA	1/2" PT
	600PFA	3/4" PT
	800PFA	1" PT
	400PMA	1/2" PT
	600PMA	3/4" PT
	800PMA	1" PT

MULTI COUPLER

SPECIFICATION

DESCRIPTION	TYPE	SMV SML SMM	SMVA SMLA SMMA	SMVT SMLT SMMT	SMLAB SMMAB
		SMY SMT SMX	SMYA SMTA SMXA	SMYT SMTT SMXT	SMTAB SMXAB
BODY		Aluminum			
COUPLER		ZDC-2	STEEL	ONE TOUCH	STEEL
Working Pressure		10 kgf/cm ²	15 kgf/cm ²		
Maximnm Pressure		15 kgf/cm ²	20 kgf/cm ²		
TERP.RANGE		-20°C ~ +80°C			
SIZE		1/4"(20TYPE)			1/2"(40TYPE)

FEATURES

- ◎ Lightweight and compact in size.
- ◎ Easy installation and storage.




SMV




SMY



SML



SMT



SMM



SMX



SM2BA



SM4BA



SM3BA



SM5BA